



K & E Chemical Co. Inc.
3960 E. 93rd St.
Cleveland OH 44105

Brick Cleaner for cleaning and preserving very dirty Brick

Klenztone®

Also used on additional surfaces such as, POLISHED STONE, UNGLAZED BRICK, FLAME FRACTURED GRANITE, FLAGSTONE, SLATE, GLAZED TERRA COTTA, UNGLAZED CERAMIC TILE **easily and economically**.

Description

KLENZTONE #4 BRICK CLEANER is the most controlled formula of KLENZTONE®. It is for use on what are both the easiest to clean and most sensitive types of masonry. The difference between it and the other formulas of KLENZTONE is that all the surfaces KLENZTONE #4 BRICK CLEANER is recommended to clean are time sensitive. This means KLENZTONE is not permitted to dry on them and, while cleaning, an **exposure time must be maintained**.

Wide Range of Surfaces

Because KLENZTONE #4 BRICK CLEANER is the formula of KLENZTONE for time sensitive surfaces, a large number of interior and exterior surfaces are recommended for cleaning with it. Of these, though, **brick** is cleaned the best. Furthermore, KLENZTONE #4 is the only formula of KLENZTONE that should ever be used on polished stone.

Easy to Use

KLENZTONE #4 BRICK CLEANER, like all formulas of KLENZTONE, does the work cleaning. It only needs to be applied, given time to work and rinsed with water. The reason KLENZTONE #4 BRICK CLEANER is not allowed to dry on time sensitive surfaces has nothing to do with its formula but, rather, is because of the surface. If the surface, you are cleaning, is one KLENZTONE #1,2 or 3 is recommended to clean, then KLENZTONE #4 BRICK CLEANER is allowed to dry on it, and conversely, if the surface is one KLENZTONE #4 BRICK CLEANER is recommended to clean, then KLENZTONE #1,2 or 3 are not allowed to dry on it.

Patch Test

Before using KLENZTONE, on the surfaces KLENZTONE #4 BRICK CLEANER is recommended to clean, **it is necessary to do a patch test**. This determines its suitability, which formula to use and an exposure time. Start with KLENZTONE #4 BRICK CLEANER, first. It almost always works best. However, if it fails to completely clean, test the next lowest formula #, working downward toward KLENZTONE #1.

Test by applying a small amount of KLENZTONE to an inconspicuous area. Do this by pouring some into a plastic dish and putting it on with a paintbrush. KLENZTONE starts working immediately, and on the easier to clean surfaces KLENZTONE #4 BRICK CLEANER is recommended for use, it usually completes cleaning quickly. Rinse KLENZTONE off, between 1 and 20 minutes, after applying and allow the test area to dry. If the surface is a completely clean and no whitish colored blush or frosting appears on the surface, use the patch test time to do your cleaning. If a whitish haze or cast does appear on the surface, then repeat the patch test, using a shorter patch test, until none does. If desired, several patch tests, of differing time lengths, can be simultaneously performed to speed up the process.

Warning: Though occurring infrequently, the white haze or frosting, KLENZTONE causes on time sensitive surfaces, is not a residue but actually forms as a part of the surface. For this reason and because the only way to remove it is to abrade it off, preventing the frosting from forming is the primary concern when cleaning time sensitive surfaces with KLENZTONE.

Problems

If a patch test fails to clean at all, it is probably because a sealer or varnish is preventing KLENZTONE from working. In this instance, strip the surface using K & E Coating Remover or another quality paint stripper first and then repeat the patch test.

Technical Data

Appearance/Odor Cloudy appearing solution with slight dull odor

Coverage 250 to 800 sq. ft./gal. can be expected depending on the porosity and condition of the surface.

Storage/Shelf Life Keep containers sealed when not in use, and store in a cool dry place. Appearance of material darkens over time, but shelf life is indefinite when properly stored.

Precautions

Adjacent areas must be properly protected when using this product. Though harmless to most building surfaces, **the damage KLENZTONE causes to glass, soft metal and glazed ceramic finishes (like those on tile and porcelain) is considered permanent.** Cover all nearby windows and aluminum with K & E Chemical's Peel Clean® Plastic Strippable Coating or thick plastic sheeting and plastic tape, and if unsure, whether KLENZTONE causes damage, test surfaces first or simply cover them. Also, **protect vegetation. KLENZTONE turns foliage brown on contact, and if drawn up through plants' roots, it dehydrates and can kill them.** Cover plants with plastic sheeting to keep concentrated KLENZTONE off foliage, and protect roots by either containing the rinse or trenching it away.

Application

Because KLENZTONE is not allowed to dry and an exposure time must be maintained, while using it on time-sensitive surfaces, the cleaning is done in sections.

- 1) **Apply KLENZTONE to a controlled area that is dry and the size of which the material can be quickly rinsed off.** Use a brush, roller and thoroughly wet the surface.
- 2) **Allow time for KLENZTONE to work.**
- 3) **Rinse the loosened grime from the surface, using the exposure time determined by your patch test.** On floors, the best way to do this is using an auto scrubber, but if one is not available, surfaces can be flood rinsed and wet vac up. Out of doors, high-pressure water is the easiest, most convenient way to rinse KLENZTONE.
- 4) **After completing rinsing, proceed to the next controlled area, and repeat the procedure.** Continue process until cleaning is complete.

Neutralizing

If impractical, cleaning in sections, large areas can be done by neutralizing the cleaner. Do this by preparing a mixture of ½ lb. soda ash per gallon of water and apply it at the time the cleaner is supposed to be rinsed. Use only enough material to make it bubble up and then stop. Once neutralized, the cleaner is inactive, and you can rinse treated surfaces at your convenience.

Limitations

Though KLENZTONE cleans virtually anything, which affects the appearance of stone & brick. It is not designed to remove graffiti or paint, nor will it remove some types of stains that occur on masonry. Graffiti and coatings can be removed using K & E Chemical's DBX® or K & E Coating Remover® paint stripper formulas, and K & E Chemical also manufactures several stain removing products.

CAUTION: Never use KLENZTONE to clean grouting on ceramic tile floors. K & E Chemical manufactures another product called CSP® Safe Grout Cleaner for this purpose. On marble tile floors, however, KLENZTONE #4 cleans grouting beautifully without etching the marble.

Safety

Wear rubber gloves, safety goggles and ventilate enclosed areas when using KLENZTONE. If it gets on skin or into eyes, rinse off immediately with water. See Material Safety Data Sheet for more detailed hazard evaluation and safety information.

Environmentally Safe

KLENZTONE is readily biodegradable and releases no V.O.C.s. When used properly, it poses no threat to the environment. Dispose of all wastes safely according to federal, state and local regulations.

Notice: The information contained herein is based on our own research and the research of others, and it is provided solely as a service to users. It is believed to be accurate to the best of our knowledge. However, no guarantee of its accuracy can be made, and it is not intended to serve as the basis for determining this product's suitability in any particular situation. For this reason, purchasers are responsible to make their own tests and assume all risks associated with using this product.

Manufactured By:

Distributed By:

K & E Chemical Co., Inc.
"The Home of KLENZTONE"
3960 E. 93rd St.
Cleveland OH 44105 (216) 341-0500